



PLF8FAY ■ Manual, Refrigerated
PLF8FAHY ■ Manual, Refrigerated, Hot 'n' Cold
PLF14FAY ■ Manual, Refrigerated
PLF14FAHY ■ Manual, Refrigerated, Hot 'n' Cold
 Drinking Fountain

PLF8FAY

Delivering 60LPH of 10°C water at 21°C ambient.
 Cooling system uses R-134a refrigerant.

PLF8FAHY

Additionally delivers Hot water.

PLF14FAY

Delivering 106LPH of 10°C water at 21°C ambient.
 Cooling system uses R-134a refrigerant.

PLF14FAHY

Additionally delivers Hot water.



These free-standing drinking fountains are manually activated via the Dial-A-Drink adjustable bubbler.

Complies with ANSI A117.1 and ADA. Shall comply with all relevant CE directives (LVD , EMC, RoHS). Shall comply with ANSI/NSF 61.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.

MODEL CODE	PLF8FAY	PLF8FAHY	PLF14FAY	PLF14FAHY
ACTIVATION	Mechanical (Dial-A-Drink Adjustable Bubbler with Flexible Bubbler Guard)			
FILTRATION	Green Filter (optional), Built-in 100 micron strainer			
DISINFECTION	Ultra Blu V (optional)			
AUTO-OFF WATER FLOW	No			
DRAINAGE TYPE	Built in drain			
EXTERIOR CHASSIS	Brushed Stainless Steel			
DIMENSIONS	1100(H) x 432(W) x 356(D) mm			
NET WEIGHT	43 kg	44kg	44 kg	45 kg
POWER SUPPLY	220-240V, 50/60 Hz			
COOLING PERFORMANCE	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)		106 LPH Rated Capacity & 60 LPH Base Rate (10°C in 21°C amb. temp.)	
FULL LOAD AMPS	2.5A	4.7A	2.5A	4.7A
RATED WATTS	320 W	820 W	320 W	820 W
ENERGY SYSTEM	Refrigeration is on only when in use or if water temp increases during long period of standby.			
COUNTRY OF ORIGIN	Mexico			
CERTIFICATIONS	ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS)			
WARRANTY	1 Year			

