



PLF4CMY ■ Manual, Non-Refrigerated
PCM ■ Manual, Non-Refrigerated
 Drinking Fountain

PLF4CMY

Delivering 30LPH of 10°C water at 21°C ambient.
 Cooling system uses R-134a refrigerant.

PCM

Delivers ambient drinking water.



These surface mount drinking fountains are manually activated via the Dial-A-Drink adjustable bubbler.

Complies with ANSI A117.1 and ADA. Shall comply with all relevant CE directives (LVD , EMC, RoHS). Shall comply with ANSI/NSF 61.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.

MODEL CODE	PLF4CMY	PCM
ACTIVATION	Mechanical (Dial-A-Drink Adjustable Bubbler with Flexible Bubbler Guard)	
FILTRATION	Green Filter (optional), Built-in 100 micron strainer	
DISINFECTION	Ultra Blu V (optional)	
AUTO-OFF WATER FLOW	No	
DRAINAGE TYPE	Built in drain	
EXTERIOR CHASSIS	Brushed Stainless Steel	
DIMENSIONS	406(H) x 432(W) x 335(D) mm	
NET WEIGHT	23 kg	11 kg
POWER SUPPLY	220-240V, 50/60 Hz	-
COOLING PERFORMANCE	30 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)	Non-Refrigerated
FULL LOAD AMPS	1.2A	-
RATED WATTS	400 W	-
ENERGY SYSTEM	Refrigeration is on only when in use or if water temp increases during long period of standby.	-
COUNTRY OF ORIGIN	Mexico	
CERTIFICATIONS	ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS)	
WARRANTY	1 Year	

