



OUTDOOR FILTER

Filtration

The Outdoor Filter is designed for higher ambient temperatures and high-capacity needs, making it ideal for water cooler applications, whether installed in a drinking fountain or in the top of OASIS bottle filler.

The Outdoor Filter withstands up to 50°C, and is an industry exclusive for the outdoor market.

It is certified to NSF/ANSI 42 for the reduction of Chlorine, Taste and Odor and Particulate Class I; NSF/ANSI 53 for the reduction of Cyst and Lead and NSF/ANSI 401 for the reduction of Microplastics.

FEATURES

- Improves the taste and appearance of drinking water
- Water filtration to reduce turbidity, dirt, rust, sediment, and to inhibit corrosion
- Automatic shut-off valve inside the head engages as filter is inserted or removed
- Filter head and cartridge engineered to withstand elevated temperatures for outdoor use
- For cold water supply line only



CERTIFICATION

- NSF/ANSI 42 for reduction of Chlorine, Taste, Odor and Particulate Class 1
- NSF/ANSI 53 for reduction of Lead and Cyst
- NSF/ANSI 401 for the reduction of Microplastics



OUTDOOR FILTER	
TEMPERATURE	2°C to 50°C
FLOW RATE	1.50 gpm (5.68 Lpm)
PRESSURE	20 psi (1.4 bar) to 125 psi (8.6 bar)
CAPACITY	17,980L
SERVICE LIFE	12 months
SEDIMENT	Down to nominal 0.5 micron
FUNCTION	Mechanical/Chemical Filtration
INSTALLATION LOCATION	For outdoor use

*When used or stored in non-temperature controlled environments, the unit must be adequately winterized and/or protected from extreme heat to prevent damage.

Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

INSTALLATION

- Rotate 1/4 turn right or left for installation or removal
- Universal kit shipped with complete instructions and mounting bracket

CERTIFICATIONS/COMPLIANCES

- NSF/ANSI 42, 53, 401 and 372

